



SPECIFICATIONS
 Current Rating: 1A AC, DC
 Voltage Rating: 50V AC, DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Solder Tabs: Phosphor Bronze/Tin-plated
 Material: Nylon 6T, UL94V-0
 Color: Natural (Beige)

1010P ** M V 0 *
 1 No. of circuits
 2 M=SMT
 3 V= Straight
 4 Packing
 0= Tape&Reel
 1= Tube

A=1.00mm*No. of spaces
 B=A+3mm

APPROVED BY		TOLERANCES	X. ±0.35	 3rd Angle Projection	 LEDCO (D.G) CO., LTD.	TITLE 1.00mm PITCH 180 WAFER-SMT TYPE	LEDCO P/N 1010P**MV0*	ERP No. AE22
CHECKED BY		X. ±0.25						
PREPARED BY	Ye Jiajia	.XX ±0.20						
DATE	2006-11-08	.XXX±0.10						
UNIT	mm	SCALE	1 : 1					
REA	A	SHEET	1 / 1					